


LAMP PHOTOMETRIC REPORT

MODEL: 93ZFLD3040/BL		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 3003.6 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	2882	3279	3427	2951	2646	2916	3379	3251	0- 10	306.3	306.3	10.2
20	2024	2660	3143	2332	1879	2317	3119	2678	10- 20	790.7	1097	36.5
30	1458	1978	2074	1623	865.6	1631	2104	1990	20- 30	985.7	2083	69.3
40	151.8	954.2	702.2	440.6	95.76	465.8	770.7	1024	30- 40	676.8	2760	91.9
50	38.14	96.24	132.5	45.13	23.88	46.61	147.0	111.9	40- 50	196.7	2956	98.4
60	12.19	15.84	26.10	9.491	7.598	9.686	27.85	17.09	50- 60	37.85	2994	99.7
70	3.523	3.586	3.517	1.541	0.6744	1.607	3.969	3.751	60- 70	8.370	3003	100
80	0.1488	0.2163	0.2101	0.1460	0.1432	0.1549	0.1883	0.1667	70- 80	0.8823	3003	100
90	0.0919	0.1033	0.1474	0.1187	0.1459	0.1699	0.1856	0.1556	80- 90	0.1593	3004	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 30 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```