


LAMP PHOTOMETRIC REPORT

MODEL: 95Livial80/WH		
POWER: 15W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 808.94 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	399.4	409.8	417.6	415.4	401.8	392.2	385.4	386.9	0- 10	38.82	38.82	4.8
20	361.3	375.5	387.9	385.2	365.9	351.9	341.7	343.8	10- 20	108.5	147.3	18.2
30	302.6	315.0	328.2	325.5	306.8	293.2	283.1	285.4	20- 30	154.6	301.9	37.3
40	232.9	241.1	252.2	250.6	235.9	225.5	217.4	219.1	30- 40	168.8	470.7	58.2
50	151.9	156.5	164.3	164.2	154.8	148.6	143.1	142.9	40- 50	149.0	619.7	76.6
60	83.80	85.37	89.21	90.21	85.86	83.11	80.00	79.20	50- 60	104.5	724.3	89.5
70	36.18	36.18	37.55	38.14	37.26	36.76	35.56	34.76	60- 70	58.11	782.4	96.7
80	8.127	7.600	7.797	8.305	8.597	9.070	9.095	8.486	70- 80	22.03	804.4	99.4
90	0.2433	0.2414	0.2351	0.2314	0.2059	0.2306	0.2488	0.2150	80- 90	4.537	808.9	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:30 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```