


LAMP PHOTOMETRIC REPORT

MODEL: 99POMX30/WH		
POWER: 20W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2345.0 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	878.6	876.6	874.8	874.5	875.7	877.2	878.6	879.1	0- 10	84.69	84.69	3.61
20	820.6	817.0	813.7	812.4	815.0	817.5	820.4	821.5	10- 20	240.1	324.8	13.8
30	730.0	725.2	720.3	718.7	722.1	727.0	730.1	741.3	20- 30	357.2	681.9	29.1
40	625.3	609.0	602.8	601.3	606.6	615.0	614.4	618.4	30- 40	420.1	1102	47
50	494.0	479.0	469.8	471.0	478.7	481.1	481.7	488.5	40- 50	422.3	1524	65
60	347.3	342.2	331.8	334.3	337.9	344.3	343.5	349.1	50- 60	368.2	1892	80.7
70	207.9	205.8	196.0	198.6	199.4	208.4	207.1	212.9	60- 70	269.8	2162	92.2
80	82.73	80.36	73.18	74.89	74.78	81.64	82.48	87.05	70- 80	147.5	2310	98.5
90	3.063	1.641	7.914	1.724	3.123	1.720	8.649	1.802	80- 90	35.36	2345	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:05 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```